

Interior Paints.

Application Procedure for Interior Paints.

1. Setting Up:

Let's Roll Starts with covering furniture - sofa, tables, cabinets, switch boards, other elements like television sets, fans, refrigerators and the floors! All wall hangings to be removed and anything that doesn't require even a drop of paint over it, to be masked. Furniture to be pulled away from the walls, making it easier to reach out to all corners.

Tools Used: Plastic Sheets, Newspapers, Masking Tape

2. Surface Preparation:

The Foundation Well prepared surface is the foundation to long lasting painting results. Loose plaster or paint flakes to be removed. Sanding is done to remove existing coat of paint and to ensure surface is dry, free from dust and dirt. Major cracks or seepage, require immediate attention and should be repaired before painting.

Tools Used: Sanding Machine, Emery Paper

3. Putty Touch up:

For Smooth Walls Putty is a white-cement based compound, applied on dry walls and ceiling, to fill in pores and smoothen the surface. Minor Holes and cracks on the surface will be filled and undulations evened out by touch ups, provided wall condition is overall good. One or two coats of putty application throughout the surface will be required, even in case of re-painting; a. When using paints with higher sheen to obtain smooth finish. In case of irregular or repaired surfaces

Tools Used: Putty Knife

4. Priming:

The Guardian Coat Primers help paint adhere to the surface, and thus improves paint coverage and creates uniform appearance in terms of colour and sheen. Priming can never be skipped, when using paints with higher sheen(gloss).

GIRIBALA CREATIVE VENTURES PVT.LTD.

CIN: U74999GJ2017PTC097068

1007, North Plaza, Near Dmart Visat Gandhinagar Highway, Motera, Ahmedabad, Gujarat, India-380005

Website: www.clickzippy.com

Download App: Click Zippy

Email: info@clickzippy.com

Mo/What's app: 99249 64118, (079)40025494

National Award for E-Governance-2019

It is always advisable to use primer, as it increases durability(life) of paint. After priming, the surface has to dry naturally for a day, before painting over.

Tools Used: Roller, Brush

5. Painting:

Finishing Touches Paints produce that final finish and colour of the surface. Before deciding on the product, end requirements in term soft functionality and appearance, must be considered. Minimum of 2 coats will be applied to achieve durable, consistent layer. Paints that produce a highly smooth finish, may require an additional coat also. Ceiling to be painted first, and then the walls. Surface needs to dry naturally after every coat. Water based paints like Emulsions that are used on walls and ceiling surfaces, dry fast (in 3 - 4 hours).

Tools Used: Roller, Brush

Why Click Zippy?

- **ASSURITY**
if any Mistake done by our professional then we can give again best services is free of cost after surety of wrong services.
- Service totally done by trained professionals within time limit that means fast services.
- Professional service is affordable rate so you can satisfied your need.
- We are based on application and website so Customer can book online services at their place and get services at doorstep.
- Easy comparison of Qualitative services and their rate.
- Broad category of services we have.

GIRIBALA CREATIVE VENTURES PVT.LTD.

CIN: U74999GJ2017PTC097068

1007, North Plaza, Near Dmart Visat Gandhinagar Highway, Motera, Ahmedabad, Gujarat, India-380005

Website: www.clickzippy.com

Download App: Click Zippy

Email: info@clickzippy.com

Mo/What's app: 99249 64118, (079)40025494

National Award for E-Governance-2019