



**Waterproofing,
Spray Machine**



**Plaster Spray
Machine**

**Gypsum Spraying
Machine**



**Fireproofing
Machine**



Machine Specifications

	Plaster Machine	Gypsum Spraying Machine	Waterproofing Machine	Fireproofing Machine	Airless Paint Spray Machine
Operating pressure max.	40 Bar	24 Bar	15 Bar	40 Bar	240 Bar
Operating Voltage	400 V / 16 A / 50 Hz	230 V / 16 A / 50 Hz	230 V / 16 A / 50 Hz	230 V / 16 A / 50 Hz	110-230V / 16A / 50Hz
Out Put	2 to 50 LPM	0 to 15 LPM	0 to 12 LPM	0 to 12 LPM	0 to 10 LPM
Delivery range	20 m	20 m	20 m	20 m	30 m
Delivery height	10 m	10 m	10 m	10 m	20 m
Material hopper	60 L	50 L	50 L	50 L	
Dimensions (LWH)	1100 X 750 X 900 mm	1100 X 550 X 900 mm	1000 X 550 X 900 mm	1000 X 550 X 900 mm	720 X 600 X 900 mm
Weight	250 Kg	150 Kg	150 Kg	150 Kg	45 Kg

Benefits of Automatic Spraying Machine

For paste and High viscose materials can spray

Very least Material Consumption

No Skill Labor required

Simple operation

Increase Productivity 10 times more than existing

Light weight, small and handy m/c.

Simple cleaning and less maintenance

Detachable SS material hopper

High performance machine